



Figure similar

SIPLUS SITOP PS MODULAR Puffermodul

SIPLUS PS modular buffer module -25...+70°C with conformal coating based on 6EP1961-3BA01 . for 6EP1x 3x-3BAX0 Buffer time 100 ms to 10 s depending on load current

Input	
supply voltage at DC rated value	24 V
voltage curve at input	DC
input voltage range	24 ... 28.8 V DC
Mains buffering	
design of the mains power cut bridging-connection	Backup time: with 40 A load current: 200 ms; with 20 A load current: 400 ms; with 10 A load current: 800 ms; with 5 A load current: 1.6 s. Reduces the backup time by 100 ms in combination with 6EP1 437-3BA10. Maximum backup time 100 ms in combination with 6EP1 336-2BA10 (load current 20 A).
Output	
formula for output voltage	$V_{in} - \text{approx. } 1 \text{ V}$
output current	
• rated value	40 A
Signaling	
display version	
• for normal operation	Green LED for "supply voltage > 20.5 V"
Interface	
product component PC interface	No
design of the interface	without
Safety	
galvanic isolation between input and output	Yes
operating resource protection class	Class III
certificate of suitability	
• CE marking	Yes
protection class IP	IP20
EMC	
standard	
• for emitted interference	EN 55022 Class B
• for interference immunity	EN 61000-6-2
environmental conditions	
ambient temperature in horizontal mounting position	-25 ... +70; with natural convection

during operation	
ambient temperature during storage and transport	-40 ... +85
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to ambient temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation acc. to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation
chemical resistance to commercially available cooling lubricants	Yes; incl. diesel and oil droplets in the air
resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust
resistance to biologically active substances conformity acc. to EN 60721-3-6	Yes; Class 6B2 mold, fungal, sponge spores (except fauna)
resistance to chemically active substances conformity acc. to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust
coating for equipped printed circuit board acc. to EN 61086	Yes; Class 2 for high availability
type of coating protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test of the coating acc. to MIL-I-46058C	Yes; Discoloration of the coating during service life possible
product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal Coating, Class A
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • at input • at output • for control circuit and status message 	screw-type terminals +: 1 screw terminal for 0.5 ... 10 mm ² -: 1 screw terminal for 0.5 ... 10 mm ² -
width of the enclosure	70 mm
height of the enclosure	125 mm
depth of the enclosure	121 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
net weight	1.2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	2 538 071 h
reference code acc. to IEC 81346-2	T
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

