

SITOP PSU100D/1AC/24VDC/12.5A

PSU100D 24 V/12.5 A Stabilized  
power supply input: 100-240 V  
AC output: DC 24 V/12,5 A

Input	
Input	1-phase AC
Rated voltage value $V_{in}$ rated	100 ... 240 V
Voltage range AC	85 ... 264 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 115/230$ V
Mains buffering at $I_{out}$ rated, min.	15 ms; at $V_{in} = 115/230$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 100 V	4 A
• at rated input voltage 240 V	2 A
Switch-on current limiting (+25 °C), max.	60 A
$I^2t$ , max.	1.1 A <sup>2</sup> ·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C or from 16 A characteristic B
Output	
Output	Controlled, isolated DC voltage
Rated voltage $V_{out}$ DC	24 V
• output voltage at output 1 at DC rated value	24 V
Total tolerance, static $\pm$	2 %
Static mains compensation, approx.	0.5 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	100 mV
Adjustment range	22 ... 28 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
Signaling	-
On/off behavior	Overshoot of $V_{out} < 2$ %
Startup delay, max.	1 s
voltage increase time of the output voltage maximum	30 ms
Rated current value $I_{out}$ rated	12.5 A
Current range	0 ... 12.5 A
• Note	+50 ... +70 °C: Derating 2.5%/K
supplied active power typical	300 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at $V_{out}$ rated, $I_{out}$ rated, approx.	86 %
Power loss at $V_{out}$ rated, $I_{out}$ rated, approx.	48 W
Closed-loop control	

Dynamic mains compensation ( $V_{in}$ rated $\pm 15\%$ ), max.	0.5 %
Dynamic load smoothing ( $I_{out}$ : 50/100/50 %), $U_{out} \pm$ typ.	5 %
<b>Protection and monitoring</b>	
Output overvoltage protection	< 35 V
Current limitation, typ.	15 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current RMS value	
• typical	15 A
Overload/short-circuit indicator	-
<b>Safety</b>	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra low output voltage $V_{out}$ according to EN 60950-1
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	1 mA
Degree of protection (EN 60529)	IP20
<b>Approvals</b>	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus (UL 60950-1, CSA C22.2 No. 60950-1), File E151273
Explosion protection	-
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
certificate of suitability EAC approval	Yes
Marine approval	-
<b>EMC</b>	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature	
• during operation	-10 ... +70 °C
— Note	with forced convection (ventilator)
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
<b>Mechanics</b>	
Connection technology	screw-type terminals
Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 1.3 mm <sup>2</sup> single-core/finely stranded
• Output	+, -: 2 screw terminals each for 0.5 ... 1.3 mm <sup>2</sup>
• Auxiliary	-
width of the enclosure	105 mm
height of the enclosure	199 mm
depth of the enclosure	41 mm
required spacing	
• top	20 mm
• bottom	0 mm
• left	20 mm
• right	20 mm
Weight, approx.	0.81 kg
Installation	Wall mounting
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)



