



SPD type 3, UN=240V AC/DC 264V AC/240V DC, UOC=6kV, 2-pol, with remote signaling, width 17,7mm

General data	
standard	IEC 61643-11: 2011, EN 61643-11: 2012
product designation	Surge protection device
SPD classification / acc. to EN 61643-11	
• Test Class I, Type 1	No
• Test Class II, Type 2	No
• Test Class III, Type 3	Yes
number of SPD ports	1
Product version	Surge arrester
design of pole	2
designation of the protective paths	L-N, L-PE, N-PE, (L+)-(L-), (L+/L-)-PE
fastening method	DIN rail NS 35
material / of the enclosure	PA 6.6-FR
size of surge arrester	1WM
Degree of pollution	2
overvoltage category / acc. to IEC 61010-1	III
protection class IP / at connection all terminals	IP20
shock acceleration	30 gn
vibrational acceleration / at 5 Hz ... 500 Hz / limited to 2,5 h / per axis	5 gn
Ambient temperature / during operation / minimum permissible ... ambient temperature / during operation / maximum permissible	-40 °C ... 80 °C
ambient temperature / during storage and transport	-40 °C ... 80 °C
relative humidity / during operation	5 % ... 95 %
installation altitude / at height above sea level / maximum	2 000 m
Width	17.7 mm
Height	90 mm
depth	74.5 mm
net weight	77 g
Electrical data	
type of distribution system	TT, TN-S
operating voltage	230 V AC
operating voltage	230 V
operating frequency	50/60 Hz
continuous operating voltage	
• maximum	264 V
• maximum	240 V

load current	26 A (30 °C)
apparent power consumption / maximum	26.4 mVA
discharge current	
• at (8/20) µs	5 kA
short-circuit rating (SCCR) / at 264 V	10 kA
protection level	
• between L and N	1.4 kV
• between L and PE	1.4 kV
• between N and L	0.2 kV
• between N and PE	1.4 kV
• between PE and N and/or L	1.4 kV
• response time / between L and (PE)N	25 ns
• response time / between N and PE	100 ns
adjustable response factor / of tripping current	1.6
fuse protection type / at V-shaped connection	25 A (gG / B / C)
insulation resistance (Riso)	5 MΩ
MPP voltage	240 V

Connections/ Terminals

type of electrical connection	Screw terminal
stripped length	10 mm
tightening torque	0.5 ... 0.5
stripped length	10 mm
connectable conductor cross-section	
• for finely stranded conductor	0.2 ... 2.5
• for rigid conductor	0.2 ... 4
• finely stranded	0.2 ... 2.5
AWG number / as coded connectable conductor cross section	30 ... 12
design of the thread / of the connection screw	M3
signal design	Defect signaling contact

Indicator/remote signaling

switching function / of the remote signaling contacts	N/C contact
operating voltage / of the remote signaling contacts	
• at AC	250 ... 250
operational current / of the remote signaling contacts	
• at AC	0.5 mA ... 0.5 A
connection type of remote signaling contact	M3
connectable conductor cross-section	
• for remote signaling contacts / for rigid conductor	0.2 ... 4
• for finely stranded conductor / for remote signaling contacts	0.2 ... 2.5
tightening torque / for remote signaling contacts	0.5 N·m
stripped length / of the cable / for remote signaling contacts	10 mm

NEMA/UL - Data

type of distribution system	TT, TN-S
TOV behavior	
• at TOV test voltage (N-PE)	1200 V (200 ms / withstand mode)
combustibility class acc. to UL 94	V0
AWG number / as coded connectable conductor cross section / according to UL / minimum	16
AWG number / as coded connectable conductor cross section / according to UL / maximum	12

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5SD7432-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SD7432-7>



