

SITOP PSU100D/1AC/12VDC/8.3A



PSU100D 12 V/8.3 A Stabilized
power supply input: 100-240 V
AC output: 12 V DC/8.3 A

Input	
Input	1-phase AC
Rated voltage value V_{in} rated	100 ... 240 V
Voltage range AC	85 ... 264 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 115/230$ V
Mains buffering at I_{out} rated, min.	15 ms; at $V_{in} = 115/230$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 100 V	2 A
• at rated input voltage 240 V	1.1 A
Switch-on current limiting (+25 °C), max.	75 A
I^2t , max.	5.5 A ² ·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C or from 16 A characteristic B
Output	
Output	Controlled, isolated DC voltage
Rated voltage V_{out} DC	12 V
• output voltage at output 1 at DC rated value	12 V
Total tolerance, static \pm	2 %
Static mains compensation, approx.	0.5 %
Static load balancing, approx.	1 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	100 mV
Adjustment range	11 ... 14 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 12 V OK
On/off behavior	Overshoot of $V_{out} < 2$ %
Startup delay, max.	1 s
voltage increase time of the output voltage maximum	30 ms
Rated current value I_{out} rated	8.3 A

Current range	0 ... 8.3 A
• Note	+50 ... +70 °C: Derating 2.5%/K
supplied active power typical	100 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
Efficiency	
Efficiency at Vout rated, Iout rated, approx.	84 %
Power loss at Vout rated, Iout rated, approx.	19 W
Closed-loop control	
Dynamic mains compensation (Vin rated ±15 %), max.	0.5 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout ± typ.	5 %
Protection and monitoring	
Output overvoltage protection	< 17.6 V
Current limitation, typ.	9.9 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current RMS value	
• typical	10 A
Overload/short-circuit indicator	-
Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra low output voltage Vout according to EN 60950-1
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	1 mA
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus (UL 60950-1, CSA C22.2 No. 60950-1), File E151273
Explosion protection	-
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
certificate of suitability EAC approval	Yes
Marine approval	-
EMC	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
• during operation	-10 ... +70 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Mechanics	
Connection technology	screw-type terminals
Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.3 ... 1.3 mm ² single-core/finely stranded
• Output	+, -: 2 screw terminals each for 0.3 ... 1.3 mm ²
• Auxiliary	-
width of the enclosure	97 mm
height of the enclosure	158 mm
depth of the enclosure	38 mm

required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	<p>20 mm</p> <p>0 mm</p> <p>20 mm</p> <p>20 mm</p>
Weight, approx.	0.57 kg
Installation	Wall mounting
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

